



BOLTING TECHNOLOGY

HYDRAULIC POWER PACK AGE / AGP series

AGE
11-230



AGP
11 (6 bar)



PH
800 bar (5m)



With electric or pneumatic drives

FEATURES:

- stepless torque adjust
- control by means of a remote controller (24V) or a compressed air control unit
- high flow pumps with the three-stage technology
- oil cooler with fan (electric models)
- overpressure safety valve
- calibrated, accurate manometer with the 1.0 accuracy class, Ø 100 mm, filled with glycerine
- automatic shutdown (electric models)
- high-pressure quick-connect couplers

reliable – durable – accurate

optimized weight – compact design – dependable – safe

For use with all types of hydraulic wrenches or hydraulic tensioners

- maximum working pressure from 800 bar to 2 000 bar
- protection class IP 54

ADDITIONAL EQUIPMENT:

- high pressure hydraulic hoses for the working pressure of 800 bar (burst pressure 3 200 bar), with quick-connect couplings, standard length of 5 m or 10 m

TECHNICAL DATA

TYPE	Power supply	Delivery [l/min]			Tank capacity [l]	Total weight ²⁾ with oil [kg]	Dimensions A x B x H [cm]
		< 70 bars	< 200 bars	< 800 bars			
AGE 02-230	230 V	3,2	0,9	0,4	1,7	17	36x23x44
AGE 05-230*	230 V	6,5	1,8	0,7	4	29	40x28x40
AGE 11-230*	230 V	8,5	3,4	1,3	4	34,5	46x30x44
AGP 11 ¹⁾	4-10 bar	4,5	1,1	0,6	3,6	22	32x31x42
AGP 28 ²⁾	4-10 bar	7,5	2,5	0,9	3,6	30	50x26x38

* unit with oil cooler

¹⁾ compressed air consumption: 1,5 m³/min

²⁾ compressed air consumption: 2,4 m³/min

³⁾ unit ready for operation (possible deviations)

The right to amend technical parameters without a prior notice is reserved.
Delivery of power packs with pneumatic drives is provided for the supply air pressure of 6 bars.